H+H Calculated Ψ-values

In accordance with BRE Report BR497 (2016) and IP 1/06 (using TRISCO version 13.0w)

PARTNERS IN WALL BUILDING

External wall junctions

E2 Other lintels (including other steel lintels)


LN001 - Independent lintels, Proprietary insulated closer (Thermabate), 30mm frame overlap

Inner leaf	Insulation thickness (mm)	Calculated Ψ-value (W/mK)					
		Insulation thermal conductivity (W/mK)					
		Part Fill (foil faced)			Full Fill		
		0.018	0.022	0.030	0.032	0.037	0.045
EW0-- 100mm Celcon Solar	50	0.046	0.047	0.048			
	75	0.049	0.048	0.048			
	100	0.051	0.050	0.050	0.039	0.040	0.041
	125				0.040	0.041	0.042
	150				0.042	0.042	0.043
EW1-- 100mm Celcon Standard	50	0.045	0.045	0.045			
	75	0.048	0.047	0.047			
	100	0.050	0.050	0.049	0.037	0.038	0.039
	125				0.039	0.040	0.040
	150				0.041	0.041	0.042
EW2-- 100mm Celcon High or Super Strength	50	0.044	0.044	0.044			
	75	0.047	0.047	0.046			
	100	0.050	0.049	0.048	0.037	0.037	0.038
	125				0.039	0.039	0.039
	150				0.041	0.041	0.041

Above Ψ-values have been based on H+H Standard Detail Drawings HH - PF - 04 for Part Fill and HH - FF - 04 for Full Fill. Deviation from these drawn details will have an affect on the calculated Ψ-values.

All calculations assume a Brick outer leaf and Plasterboard on dabs internal finish

All details have calculated temperature factors (f) which are not less than the BRE IP 1/06 critlcal temperature factor of 0.75



H+H UK Limited, Technical Services Department, Celcon House, Ightham, Sevenoaks, Kent TN15 9HZ
Tel: 01732 880580 e-mail: tsd@hhcelcon.co.uk